The PSU 130 is a compact, lightweight benchtop power supply. Designed as an affordable yet highly functional piece of lab equipment, the PSU 130 will be commonplace in Engineering/Test departments worldwide.





Features

- Wide input voltage range : 100 240 Va.c. / 47 63 Hz
- Continuously variable 1.5 to 30V d.c. regulated output
- 0 to 1A output current
- Over-voltage, over-current and short-circuit protection
- Excellent regulation, low ripple
- Independent digital voltage and current indication with LED backlighting

- High efficiency design with low heat output
- Supplied with screw terminal adaptor block
- Standard test lead connections on 19 mm (0.75") spacing
- Compact: 135 x 140 x 53 mm (5.3 x 5.5 x 2.1")
- Lightweight: 520g (18.3oz)

Functions



- 1 Standard Worldwide AC power input supplied with either UK, US or Euro lead.
- **ON/OFF** isolation switch.
- Standard 4mm terminals on a 19mm pitch recessed for safety.
- 4 Adjustable output potentiometer with a firm ¾ turn (270°) action.
- **6** Orange backlit LCD providing clear indication of voltage and current.
- **6** Stylish enclosure design.
- Full UL / CE approval.

| Specification | Min | Тур | Max | Unit |
|---|-----|-----|------|--------------------|
| Input voltage | 100 | | 240 | V a.c. |
| Input frequency | 47 | | 63 | Hz |
| Input current | 50 | | 650 | mA _{.m} , |
| Safety ground leakage current (@220 V a.c. / 50 Hz) | | 0.3 | | mA |
| Output voltage | 1.5 | | 30 | V d.c. |
| Maximum output current | | 1.2 | | A d.c. |
| Line regulation - (10% line voltage change) | | | 1 | % |
| Ripple and Noise, 20MHz BW | | | 100 | m∨ p-p |
| Operating temperature* | 0 | | + 40 | °C |
| Storage temperature* | -10 | | +60 | °C |

^{*} at <75% RH, non condensing

Please note that all specifications are correct at time of print. The Company reserves the right to change any specification, typographical, clerical or other error or omission without any liability on the part of the company.



Lascar Electronics (HK) Limited